



# ORMONOID

EST. 1912

# BITUMEN PAINT

A multi purpose bituminous product supplied in a paint consistency. Applicable as an adhesive primer, coating or for tree surgery



## FEATURES AND BENEFITS

- Easily spread and quick drying
- Resistant to mild acids, alkali, moisture, air and vermin
- Will not harm trees when sealing wounds
- Can be overpainted with Ormonoid Silvershield™ or an oil based paint for U.V. protection and better appearance

## PACKAGING

Available in a 500ml, 1L or 4L tin

## USES

- To adhere bituminous roofing to concrete and timber surfaces
- As a primer on concrete, fibro, metal and other porous surfaces prior to the application of bituminous products
- For protection of exterior metal surfaces such as guttering, downpipes, water tanks, troughs, trailers, car bodies and metal type roofing against corrosion
- Sealing of tree wounds after pruning, to prevent disease or vermin attack

## PRODUCT INFORMATION

### Coverage

**As an adhesive**

Approximately 4m<sup>2</sup>/L

**As a primer**

Approximately 7m<sup>2</sup>/L

**As a coating**


Approximately 7m<sup>2</sup>/L

### Shelf Life

Approximately 12 months in unopened containers stored in a cool, dry place



MADE IN AUSTRALIA



## DIRECTIONS FOR USE

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from grease, oil, wax or any loose contaminating material
- New metal surfaces should be allowed to weather for a minimum of three months prior to coating
- Over rusted surfaces it is essential to remove loose rust or scale, wire brushing will do, prior to coating

### MIX PREPARATION

#### Mix Process

Stir contents thoroughly before and during use.

## APPLICATION

### As an adhesive for roofing rolls

- Apply sparingly by brush to both surfaces, press to exclude any air pockets and to maximise adhesion

### As a primer

- Apply liberally with paintbrush or broom

### As a coating

- Apply by brush, roller or spray gun, allow 24 hours between further coats if required

### As a tree sealer

- Apply by brush directly to the affected area

## Clean-up & Return to Service

- Mineral turps can be used to clean up excess product and tools

## PRECAUTIONS

- SDS is available from [www.parexdavco.com.au/ormonoid](http://www.parexdavco.com.au/ormonoid)
- Not suitable for use or as waterproofing membrane / coating
- Do not use in exposed situations, as U.V. rays can affect it. Therefore it must be overpainted with Ormonoid Silvershield™


## TECHNICAL DATA

TECHNICAL DATA	ORMONOID BITUMEN PAINT
Appearance	A thin black liquid, with a strong solvent odor
Solids content	Above 35%
U.N. number	1993
Packaging group	III
Dangerous goods class	3
Poisons schedule number	5



Quality  
ISO 9001  
SAI GLOBAL

ParexGroup products manufactured in Australia are produced in accordance with quality management systems certified as complying with AS/NZS ISO 9001:2008.



The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3958.1 - 1991.

The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.