



# Rejuvenation Grout



A ready to use grout designed to be applied straight over existing grout



## WHERE TO USE

### Surfaces

Most common substrates.

### Tiles

Suitable for glossy and smooth tiles only. Grout joints with at least 1mm of depth from the existing grout surface to the top of the tile.

**Note:** Do not use on flush joints or highly textured and / or porous tiles.

### Areas

Suitable for interior and exterior applications. Commercial and domestic walls and floors including pools and submerged areas.

## FEATURES & BENEFITS

- Ready to use
- Suitable for use in pools
- Easy and fast application
- Stain, mould and bacteria resistant

## PACKAGING

Available in a 1.7kg pail

## AVAILABLE COLOURS



Picket Fence



Platinum



Thunderbolt



Antique Lace



Fossil



Abyss

## PRODUCT INFORMATION

### VOC Content

Low VOC - 2g/L (SCAQMD method 304-91)

### Coverage

1.7kg pail of Davco Rejuvenation Grout covers approximately 20m<sup>2</sup> (based on 200 x 200mm tiles with a 4mm wide by 1mm deep grout joint)

### Curing Time

Dry area 12 hours

Wet area 48 hours

Submerged area 7 days



MADE IN AUSTRALIA



## DIRECTIONS FOR USE

- Test the grout in an inconspicuous area first
- You will need a firm but flexible grout float or squeegee, a large tiler's sponge and a bucket of clean water
- Plan the area to be grouted, you should only grout up to 1m<sup>2</sup> at a time
- Start by working backwards out of corners

## SURFACE PREPARATION

- All surfaces must be installed according to manufacturer's instructions and relevant Australian Standard(s) and be structurally sound, dry, clean and free from movement, oil, grease, wax, sealers, curing compounds, release agents and any other loose or contaminating material
- The tile and grout surface must be thoroughly cleaned with either a mild soap and water mixture or sugar soap mixture. If required, a bristle brush can be used to clean the existing grout joints
- Rinse surface with clean water to ensure there is no residue on the surface and allow the surface to completely dry prior to application of Rejuvenation Grout

## APPLICATION

1. Stir thoroughly before use. Apply to the grout joint and using the float or squeegee, spread diagonally across the joint. Ensure you are filling the joint evenly. Only cover 1m<sup>2</sup> at a time as Rejuvenation Grout will be difficult to clean off once it dries.
2. After approximately 5-10 minutes, clean off excess grout and evenly shape the grout joints by laying a damp sponge on the tile surface and lightly wiping in a circular motion.
3. Finish the application with a single diagonal wipe to the tile surface with a well wrung sponge. Avoid applying excessive force or repeatedly wiping as this may remove the grout from the joint. If the water in the bucket becomes dirty, replace with clean water.

## Clean-up & Return to Service

- After the grout sets (approx. 30 minutes), some grout haze may still remain on the tiles. With clean water and a very well wrung sponge, wipe the tile surface in a circular, buffing motion, avoiding the grout joints

## PRECAUTIONS

### Safety

- SDS is available from [www.parexdavco.com.au](http://www.parexdavco.com.au)
- It is recommended that applicators wear PVC or similar gloves and safety goggles while handling this product
- Keep out of reach of children. If eye contact occurs, rinse with cool water. If ingested get immediate medical assistance

### General

- Do not apply in temperatures above 35°C or below 5°C
- In cool and / or humid conditions, allow longer setting times

### Specific

- Rejuvenation Grout is not recommended for use on highly textured or porous tiles due to its high bond strength
- Existing grout must be at least 1mm below the surface of the tile, allowing sufficient depth for the Rejuvenation Grout to bond to the grout joint
- Alternatively rake out sufficient grout to allow 1mm depth
- Do not allow the Rejuvenation Grout to skin / dry out in the tub. Always replace the plastic film after use
- Do not use acidic cleaners on Rejuvenation Grout
- When used in pools the pH of the water must remain between 6 and 8
- For other uses not mentioned in these instructions, please contact ParexGroup

## TECHNICAL DATA

TECHNICAL DATA	REJUVENATION GROUT
Appearance	Coloured paste
Curing time before return to dry area service	12 hours
Curing time before return to wet area service	48 hours
Curing time before return to submerged area service	7 days
Shelf life when stored unopened in elevated, cool, dry location	12 months

All measurements are taken at 22°C and 50% relative humidity. Specifications vary according to site conditions and should be taken as a guide only.



Quality  
ISO 9001  
SAI GLOBAL

ParexGroup products manufactured in Australia are produced in accordance with quality management systems certified as complying with AS/NZS ISO 9001:2008.



1800 653 347



[parexdavco.com.au](http://parexdavco.com.au)



[technical@parexdavco.com.au](mailto:technical@parexdavco.com.au)



[facebook.com/ParexDavco](https://facebook.com/ParexDavco)

ParexGroup reserves the right to inspect any alleged failure at our cost. No responsibility will be accepted unless a representative of ParexGroup is afforded the opportunity to inspect any alleged failure.



**PAREXGROUP**  
Building expertise, together