

Davco



Product Data Sheet

Sanitized[®] Tile & Grout Sealer



A solvent-based sealer that helps protect against stains, soiling, discolouration and efflorescence



WHERE TO USE

Surfaces

Only suitable for cement-based grouts. Can also be used over most unglazed porous ceramic tiles.

Areas

Suitable for interior and exterior applications. Commercial and domestic walls and floor grout joints.

PRODUCT INFORMATION

Coverage

Davco Sanitized[®] Tile & Grout Sealer approximately 6-10m²/L (depending upon surface porosity and site conditions)

Drying Time

24 hours at 22°C

FEATURES & BENEFITS

- Clear solution which cures to an invisible, water repellent coating
- Easy to apply

PACKAGING

Available in a 500ml can



MADE IN AUSTRALIA



PRECAUTIONS

Safety

- SDS is available from www.parexdavco.com.au

Specific

- Do not flood the floor with Sanitized® Tile & Grout Sealer. Apply only in small sections and clean up the area before moving on
- Do not allow excess sealer to dry on the surface of the tiles as it will leave a white residue
- For other uses not mentioned in these instructions, please visit www.parexdavco.com.au

DIRECTIONS FOR USE

- Test product in an inconspicuous area first

SURFACE PREPARATION

- Ensure grout joints and tile surfaces are thoroughly dry, clean, free from dirt, dust, grease, oil, wax and other contaminants

APPLICATION

1. Apply using a sponge, brush or spray gun.
2. Allow 5-10 minutes for the sealer to penetrate the surface, then wipe off excess with a damp sponge.
3. Allow the sealer to cure for 24 hours prior to putting the area in use.

Note: If only sealing grout joints of porous ceramic or terracotta tiles, ensure clean up method is pre-tested. It may be necessary to mask the joints

Clean-up & Return to Service

- Excess Sanitized® Tile & Grout Sealer and tools can be cleaned up with mineral turps while the product is still wet

TECHNICAL DATA	TILE & GROUT SEALER
Appearance	Clear liquid
Coverage based on surface porosity and site conditions	6-10m ² /L
Specific gravity	1.0kg/L
Drying time	24 hours
Shelf life when stored unopened in elevated, cool, dry location	12 months

All measurements are taken at 22°C and 50% relative humidity. Specifications vary according to site conditions and should be taken as a guide only.



ParexGroup products manufactured in Australia are produced in accordance with quality management systems certified as complying with AS/NZS ISO 9001:2008.

